

Data Sheet

FUJITSU Server PRIMERGY RX350 S8 Dual Socket 4U rack server

Maximum expandability in a 2 way server

FUJITSU Server PRIMERGY systems provide the most powerful and flexible data center solutions for companies of all sizes, across all industries and for any type of workload. This includes expandable PRIMERGY tower servers for remote and branch offices, versatile rack-mount servers, compact and scalable blade systems, as well as density-optimized scale-out servers. They convince by business proven quality with a wide range of innovations, highest efficiency cutting operational cost and complexity, and provide more agility in daily operations in order to turn IT faster into a business advantage.

FUJITSU Server PRIMERGY RX rack systems are versatile rack-optimized servers providing best-in-class performance and energy efficiency, and thus form the "standard" in each datacenter. PRIMERGY RX servers deliver 20 years of development and production know-how resulting in extremely low failure rates below market average, and leading to continuous operations and outstanding hardware availability.

PRIMERGY RX350 S8

The Fujitsu Server PRIMERGY RX350 S8 is a 4U rack server with maximum levels of performance, expandability and availability. It combines the performance of Intel® Xeon® processors E5 family with up to two graphics processing units (GPU) for computationally intensive applications. The new modular concept supports excellent expandability with up to 24 hard disk drives, up to 10 PCIe Gen 3 cards and up to 1536 GB memory. Moreover the 4 hot-plug, power supply units with up to 96% efficiency and the new power management, will result in lower operational costs. Thanks to the upgrade kits as well as the cost-saving Modular LAN options, the RX350 is prepared for future requirements. RX350 is ideal for database, consolidation or high performance computing scenarios.



Features & Benefits

Main Features	Benefits
Meet today's demand and be prepared for future requirements ■ Intel Xeon E5-2600 v2 product family with up to 12 core processors and Turbo Boost 2.0 ■ Up to 2 NVIDIA® GPU cards or Intel® Xeon® Phi™ cards Lifecycle investment protection ■ Expanded scalability of up to 24 DIMMs with 1536 GB memory, up to 24 hard disk drives and 10 PCIe slots ■ New modular concept for the base unit as well as a choice for LAN controller, RAID controller and power supplies ■ Upgrade kits for hard disk drives, backup devices as well as LTO drives Cost efficient operations ■ Comprehensive power management including pre-defined power profiles and a scheduled mode to switch between the profiles automatically ■ 4 hot-plug PSU with 94 % efficiency (96 % planned) ■ Fujitsu ServerView Suite offers tools for installation and deployment, permanent status monitoring and control. A wide range of integration packs allow a seamless and easy integration in widely-used enterprise management systems.	■ High performance for an efficient datacenter ■ 50% more cores compared to the previous generation enables to run significantly more virtual machines ■ Optimized for business applications, cloud and virtualization as well as for computationally intensive applications, e.g. high performance computing (HPC) or computer tomography ■ Maximum expandability to meet future demand ■ Individual and cost-saving configuration of the server according to the need of today with upgrade option to meet the demand of tomorrow ■ Upgrade kits save budget as the system can be upgraded when the company grows and thus protect the investment ■ Ability to protect the data by integrating backup devices ■ Simplified power management that adjust the power consumption accordingly to the current usage or to the given power policy ■ Fujitsu ServerView Suite provides all the functions for fail-safe, flexible and automated 24x7 server operations and improves end-user productivity via intelligent and innovative system management solutions.

Technical details

PRIMERGY RX350 S8

Base unit	PRIMERGY RX350 S8 LFF	PRIMERGY RX350 S8 SFF
Housing types	Rack	Rack
Storage drive architecture	3.5-inch	2.5-inch
Power supply	Hot-plug	Hot-plug

Mainboard

Mainboard type	D2949
Chipset	Intel® C600 (Patsburg A)
Processor quantity and type	1 - 2 x Intel® Xeon® processor E5-2600 v2 product family

Processor

Intel® Xeon® processor E5-2603v2 (4C/4T, 1.80 GHz, TLC: 10 MB, Turbo: No, 6.4 GT/s, Mem bus: 1,333 MHz, 80 W)
Intel® Xeon® processor E5-2609v2 (4C/4T, 2.50 GHz, TLC: 10 MB, Turbo: No, 6.4 GT/s, Mem bus: 1,333 MHz, 80 W)
Intel® Xeon® processor E5-2620v2 (6C/12T, 2.10 GHz, TLC: 15 MB, Turbo: 2.40 GHz, 7.2 GT/s, Mem bus: 1,600 MHz, 80 W)
Intel® Xeon® processor E5-2630Lv2 (6C/12T, 2.40 GHz, TLC: 15 MB, Turbo: 2.60 GHz, 7.2 GT/s, Mem bus: 1,600 MHz, 60 W)
Intel® Xeon® processor E5-2630v2 (6C/12T, 2.60 GHz, TLC: 15 MB, Turbo: 2.90 GHz, 7.2 GT/s, Mem bus: 1,600 MHz, 80 W)
Intel® Xeon® processor E5-2637v2 (4C/8T, 3.50 GHz, TLC: 15 MB, Turbo: 3.60 GHz, 8.0 GT/s, Mem bus: 1,866 MHz, 130 W)
Intel® Xeon® processor E5-2640v2 (8C/16T, 2.00 GHz, TLC: 20 MB, Turbo: 2.30 GHz, 7.2 GT/s, Mem bus: 1,600 MHz, 95 W)
Intel® Xeon® processor E5-2643v2 (6C/12T, 3.50 GHz, TLC: 25 MB, Turbo: 3.40 GHz, 8.0 GT/s, Mem bus: 1,866 MHz, 130 W)
Intel® Xeon® processor E5-2650Lv2 (10C/20T, 1.70 GHz, TLC: 25 MB, Turbo: 1.90 GHz, 8.0 GT/s, Mem bus: 1,600 MHz, 70 W)
Intel® Xeon® processor E5-2650v2 (8C/16T, 2.60 GHz, TLC: 20 MB, Turbo: 3.00 GHz, 8.0 GT/s, Mem bus: 1,866 MHz, 95 W)
Intel® Xeon® processor E5-2660v2 (10C/20T, 2.20 GHz, TLC: 25 MB, Turbo: 2.60 GHz, 8.0 GT/s, Mem bus: 1,866 MHz, 95 W)
Intel® Xeon® processor E5-2667v2 (8C/16T, 3.30 GHz, TLC: 25 MB, Turbo: 3.60 GHz, 8.0 GT/s, Mem bus: 1,866 MHz, 130 W)
Intel® Xeon® processor E5-2670v2 (10C/20T, 2.50 GHz, TLC: 25 MB, Turbo: 2.90 GHz, 8.0 GT/s, Mem bus: 1,866 MHz, 115 W)
Intel® Xeon® processor E5-2680v2 (10C/20T, 2.80 GHz, TLC: 25 MB, Turbo: 3.10 GHz, 8.0 GT/s, Mem bus: 1,866 MHz, 115 W)
Intel® Xeon® processor E5-2690v2 (10C/20T, 3.00 GHz, TLC: 25 MB, Turbo: 3.30 GHz, 8.0 GT/s, Mem bus: 1,866 MHz, 130 W)
Intel® Xeon® processor E5-2695v2 (12C/24T, 2.40 GHz, TLC: 30 MB, Turbo: 2.80 GHz, 8.0 GT/s, Mem bus: 1,866 MHz, 115 W)
Intel® Xeon® processor E5-2697v2 (12C/24T, 2.70 GHz, TLC: 30 MB, Turbo: 3.00 GHz, 8.0 GT/s, Mem bus: 1,866 MHz, 130 W)

Memory slots	24 (12 DIMMs per CPU, 4 channels with 3 slots per channel)
Memory slot type	DIMM (DDR3)
Memory capacity (min. - max.)	4 GB - 1536 GB
Memory protection	Advanced ECC Memory Scrubbing SDDC (Chipkill™) Rank sparing memory support Memory Mirroring support

Memory notes	Max. 8 memory modules/CPU with UDIMM (low voltage or standard) OR quad-rank RDIMM; max. 12 memory modules/CPU with single or dual-rank RDIMM or single, dual-rank or quad-rank Load-Reduced (LR) DIMM. Memory Mirroring with identical modules in both channel pairs of a bank (4 modules per bank), Rank sparing or Performance Mode with identical modules in all four channels (4 modules per bank).
--------------	--

Memory options

4 GB (1 module(s) 4 GB) DDR3 LV, registered, ECC, 1,600 MHz, PC3-12800, DIMM, single rank
8 GB (1 module(s) 8 GB) DDR3 LV, registered, ECC, 1,600 MHz, PC3-12800, DIMM, single rank
8 GB (1 module(s) 8 GB) DDR3, registered, ECC, 1,866 MHz, PC3-14900, DIMM, dual rank
16 GB (1 module(s) 16 GB) DDR3 LV, registered, ECC, 1,600 MHz, PC3-12800, DIMM, dual rank
16 GB (1 module(s) 16 GB) DDR3, registered, ECC, 1,866 MHz, PC3-14900, DIMM, dual rank
32 GB (1 module(s) 32 GB) DDR3 LR, registered, ECC, 1,866 MHz, PC3-14900, DIMM, 4Rx4
32 GB (1 module(s) 32 GB) DDR3 LV, registered, ECC, 1,600 MHz, PC3-12800, DIMM, quad rank
64 GB (1 module(s) 64 GB) DDR3 LR, registered, ECC, 1,333 MHz, PC3-10600, DIMM, octo rank

Memory options

8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1,600 MHz, PC3-12800, DIMM, dual rank
--

Interfaces

USB 2.0 ports	10 x USB 2.0 (2x front, 4x rear, 2x internal for backup devices, 1x USB stick, 1x USSD)
---------------	---

Interfaces

Graphics (15-pin)	2 x VGA (thereof 1x front optional)
Serial 1 (9-pin)	1 x serial RS-232-C, usable for iRMC or system or shared
LAN / Ethernet	2 x Gbit/s Ethernet (RJ45) with upgrade options for additional 2x1 Gbit/s (RJ45), 4x 1 Gbit/s (RJ45) or 2x 10 Gbit/s (SFP+)
Management LAN (RJ45)	1 x dedicated management LAN port for iRMC S4 (10/100/1000 Mbit/s) Management LAN traffic can be switched to shared onboard Gbit LAN port or optional Modular LAN 2x10 Gbit controller Front Service LAN port as option

Onboard or integrated Controller

RAID controller	4 port for internal 3G SATA and SAS (as upgrade option with SAS enabling key) for HDDs with RAID 0/1/10 or SAS LTO device (Intel C600) additional RAID controller options are described under Components RAID controller
SATA Controller	Intel® C600, 2 x SATA channel for ODD
LAN Controller	Intel® Ethernet Controller I350. 2 x 10/100/1000 Mbit/s Ethernet (I/O acceleration). Modular integrated on-board LAN offers upgrade options for additional 2x1 Gbit/s, 4x 1 Gbit/s or 2x 10 Gbit/s. PXE-Boot via LAN from PXE server, iSCSI boot (also diskless)
Remote management controller	Integrated Remote Management Controller (iRMC S4, 256 MB attached memory incl. graphics controller) IPMI 2.0 compatible
GPU / coprocessor	1-2 NVIDIA® Tesla™ K20 and K20X GPGPU 1-2 Intel® Xeon® Phi 3120P / 5110P / 7120P coprocessor
Trusted Platform Module (TPM)	Infineon / separate module; TCG V1.2 compliant (option)

Slots

PCI-Express 3.0 x4 (mech. x8)	2 x Full height (2nd processor required)
PCI-Express 3.0 x8	4 x Full height (here of 1 is reserved for Modular RAID controller)
PCI-Express 3.0 x8 (mech. x16)	1 x Full height
PCI-Express 3.0 x16	2 x Full height (2nd processor required)
PCI-Express 2.0 x4 (mech. x8)	1 x Full height (2nd processor required)
Slot Notes	One PCIe Gen3 x8 slot may be occupied with a Modular integrated on-board LAN controller if configured. One PCIe Gen3 x8 slot may be occupied with a modular RAID controller if configured. Important: 5 PCIe slots are supported with the first processor. 10 PCIe slots are supported with two processors. Possible slot length described in relevant system configurator.

Drive bays

Storage drive bays	2.5-inch or 3.5-inch hot-plug SAS/SATA
Accessible drive bays	1 x 5.25/0.5-inch for ODD 1 x 5.25/1.6-inch for ODD or backup devices 1 x 5.25/0.5-inch for Local Service Display
Notes accessible drives	All possible options described in relevant system configurator.

Drive bays

Storage drive bays	Max 12 (4 + 4 + 4) x 3.5-inch	Max 24 (8 + 8 + 8) x 2.5-inch
Optional accessible drives	3x 5.25/1.6-inch bay for accessible devices (HDD: 4x 3.5-inch hot-plug SAS/SATA or LTO drive)	3x 5.25/1.6-inch bay for accessible devices (HDD: 8x 2.5-inch hot-plug SAS/SATA and LTO drive)

General system information

Number of fans	4
Fan configuration	4x single hot plug fans Ø90mm plus optional 2x single hot plug fans Ø90mm for redundancy

Operating panel

Operating buttons	On/off switch Reset button NMI button ID button
-------------------	--

Operating panel

Status LEDs	System status (orange / yellow) Identification (blue) Hard disks access (green) Power (amber / green) At system rear side: System status (orange / yellow) Identification (blue) LAN connection (green) LAN speed (green / yellow)
Service display	Optional: ServerView Local Service Display (LSD)

BIOS

BIOS features	ROM based setup utility Recovery BIOS BIOS settings save and restore Local BIOS update from USB device Online update tools for main Windows and Linux versions Local and remote update via ServerView Update Manager SMBIOS V2.4 Remote PXE boot support Remote iSCSI boot support
----------------------	--

Operating Systems and Virtualization Software

Certified or supported operating systems and virtualization software	Microsoft® Hyper-V Server 2012 R2
	Microsoft® Windows Server® 2012 R2 Datacenter
	Microsoft® Windows Server® 2012 R2 Standard
	Microsoft® Windows Storage Server 2012 R2 Standard
	Microsoft® Hyper-V Server 2012
	Microsoft® Windows Server® 2012 Datacenter
	Microsoft® Windows Server® 2012 Standard
	Microsoft® Windows Storage Server 2012 Standard
	Microsoft® Hyper-V™ Server 2008 R2
	Microsoft® Windows Server® 2008 R2 Datacenter
	Microsoft® Windows Server® 2008 R2 Enterprise
	Microsoft® Windows Server® 2008 R2 Standard
	Microsoft® Windows® Web Server 2008 R2
	Microsoft® Windows® Small Business Server 2011 Premium Add-On
	Microsoft® Windows® Small Business Server Standard 2011
	Microsoft® Windows® Server 2008 Datacenter
	Microsoft® Windows® Server 2008 Enterprise
	Microsoft® Windows® Server 2008 Standard
	Microsoft® Windows® Web Server 2008
	VMware vSphere™ 5.5
	VMware vSphere™ 5.1 Embedded
	VMware vSphere™ 5.1
	VMware vSphere™ 5.0 Embedded
	VMware vSphere™ 5.0
	SUSE® Linux Enterprise Server 12
	SUSE® Linux Enterprise Server 11
	Red Hat® Enterprise Linux 7
	Red Hat® Enterprise Linux 6
	Red Hat® Enterprise Linux 5
	Red Hat® Enterprise Linux 5 with XEN
	Citrix® XenServer®

Operating system release link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473
--------------------------------------	---

Operating system notes	Support of other Linux derivatives on demand
-------------------------------	--

Server Management

Standard	ServerView Suite - Deploy SV Installation Manager SV Scripting Toolkit ServerView Suite - Control Operations Manager incl. PDA and ASR & R (Prefailure and Analysis; Automatic Server Recovery and Restart) Agents and CIM Providers System Monitor RAID Manager Capacity Management Power Management Storage Support ServerView Suite - Maintain Remote Management (iRMC) Update Management (BIOS, Firmware, Windows Drives and SV Agents) Performance Measurement Asset Management Online Diagnostics ServerView Suite - Integrate Integration packs e.g. for Microsoft System Center, VMware vCenter, Nagios, HP SIM and others Deployment Solutions and others
Option	ServerView Suite - Maintain iRMC Advanced Pack incl. Advanced Video Redirection (AVR), video capturing and Virtual Media ServerView Suite - Dynamize Virtual-IO Manager (VIOM) Resource Orchestrator Virtual Edition (ROR VE) Resource Orchestrator Cloud Edition (ROR CE) ServerView Suite - Integrate Integration pack for Fujitsu ManageNow® solution
Server Management notes	Regarding dependencies for ServerView Suite software products see dedicated product data sheets.
Dimensions / Weight	
Rack (W x D x H)	482.6 mm (Bezel) / 448 mm (Body) x 736 x 177 mm
Mounting Depth Rack	700 mm
Height Unit Rack	4 U
19" rackmount	Yes
Weight	up to 35 kg
Weight notes	Actual weight may vary depending on configuration
Rack integration kit	Rack integration kit as option
Environmental	
Operating ambient temperature	10 - 35 °C
Operating relative humidity	10 - 85 % (non condensing)
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Noise emission	Measured according to ISO 7779 and declared according to ISO 9296
Sound pressure (LpAm)	Minimum noise : 24 dB(A) (idle) / 25 dB(A) (operating) Typical noise : 27 dB(A) (idle) / 27 dB(A) (operating)
Sound power (LWAd; 1B = 10dB)	Minimum noise : 4,1 B (idle) / 4,2 B (operating) Typical noise : 4,4 B (idle) / 4,5 B (operating)
Noise notes	Noise emissions and operation modes depend on system configuration.
Electrical values	
Power supply configuration	1-4x 450 W / 800 W hot-plug power supply
Max. output of single power supply	450 W (94 % efficiency); 800 W (94 % / 96 % efficiency)
Power supply efficiency	94 % (80 PLUS platinum) 96 % (80 PLUS titanium)
Hot-plug power supply output	450 W (94 % efficiency); 800 W (94 % / 96 % efficiency)
Hot-plug power supply redundancy	Yes
Rated voltage range	100 V - 240 V

Electrical values

Rated frequency range	47 Hz - 63 Hz
Rated current in basic configuration	100 V - 240 V / TBD
Active power (max. configuration)	1,070 W
Active power note	To estimate the power consumption of different configurations use the Power Calculator of the System Architect: http://configurator.ts.fujitsu.com/public/
Apparent power (max. configuration)	1,080 VA
Heat emission	3852.0 kJ/h (3651.0 BTU/h)
Power Supply Notes	Power Safeguard adapts system performance in case the wattage exceeds supply limits.

Compliance

Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment)
Germany	GS
Europe	CE Class A *
USA/Canada	CSA/cus FCC Class A
Japan	VCCI
China	CCC (planned)
Australia/New Zealand	C-Tick
Taiwan	CNS 13438 class A - planned
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request. * Warning: This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Components

Storage drives

SSD SATA, 6 Gb/s, 800 GB, Read-Intensive Endurance, hot-plug, 3.5-inch, enterprise
SSD SATA, 6 Gb/s, 800 GB, Read-Intensive Endurance, hot-plug, 2.5-inch, enterprise
SSD SATA, 6 Gb/s, 800 GB, Mainstream Endurance, hot-plug, 3.5-inch, enterprise
SSD SATA, 6 Gb/s, 800 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
SSD SATA, 6 Gb/s, 480 GB, Read-Intensive Endurance, hot-plug, 3.5-inch, enterprise
SSD SATA, 6 Gb/s, 480 GB, Read-Intensive Endurance, hot-plug, 2.5-inch, enterprise
SSD SATA, 6 Gb/s, 400 GB, Mainstream Endurance, hot-plug, 3.5-inch, enterprise
SSD SATA, 6 Gb/s, 400 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
SSD SATA, 6 Gb/s, 240 GB, Read-Intensive Endurance, hot-plug, 3.5-inch, enterprise
SSD SATA, 6 Gb/s, 240 GB, Read-Intensive Endurance, hot-plug, 2.5-inch, enterprise
SSD SATA, 6 Gb/s, 200 GB, Mainstream Endurance, hot-plug, 3.5-inch, enterprise
SSD SATA, 6 Gb/s, 200 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
SSD SATA, 6 Gb/s, 120 GB, Read-Intensive Endurance, hot-plug, 3.5-inch, enterprise
SSD SATA, 6 Gb/s, 120 GB, Read-Intensive Endurance, hot-plug, 2.5-inch, enterprise
SSD SATA, 6 Gb/s, 100 GB, MLC, hot-plug, 2.5-inch, enterprise
SSD SATA, 6 Gb/s, 100 GB, Mainstream Endurance, hot-plug, 3.5-inch, enterprise
SSD SATA, 6 Gb/s, 100 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
SSD SAS, 12 Gb/s, 800 GB, Mainstream Endurance, hot-plug, 3.5-inch, enterprise
SSD SAS, 12 Gb/s, 800 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
SSD SAS, 12 Gb/s, 400 GB, Mainstream Endurance, hot-plug, 3.5-inch, enterprise
SSD SAS, 12 Gb/s, 400 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
SSD SAS, 12 Gb/s, 200 GB, Mainstream Endurance, hot-plug, 3.5-inch, enterprise
SSD SAS, 12 Gb/s, 200 GB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
SSD SAS, 12 Gb/s, 1.6 TB, Mainstream Endurance, hot-plug, 3.5-inch, enterprise
SSD SAS, 12 Gb/s, 1.6 TB, Mainstream Endurance, hot-plug, 2.5-inch, enterprise
PCIe-SSD, 785 GB, MLC, Flash drive, 7.7 DWPD (drive writes per day)
PCIe-SSD, 365 GB, MLC, Flash drive, 6 DWPD (drive writes per day)
PCIe-SSD, 1.2 TB, MLC, Flash drive, 7.7 DWPD (drive writes per day)
HDD SATA, 6 Gb/s, 500 GB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 500 GB, 7,200 rpm, hot-plug, 2.5-inch, business critical
HDD SATA, 6 Gb/s, 250 GB, 7,200 rpm, hot-plug, 2.5-inch, business critical
HDD SATA, 6 Gb/s, 3 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 2 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SATA, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 2.5-inch, business critical
HDD SAS, 6 Gb/s, 900 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 600 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 6 Gb/s, 600 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 600 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 500 GB, 7,200 rpm, hot-plug, 2.5-inch, business critical
HDD SAS, 6 Gb/s, 450 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 6 Gb/s, 450 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 450 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 15,000 rpm, hot-plug, 3.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 146 GB, 15,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 4 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 6 Gb/s, 3 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 6 Gb/s, 2 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 6 Gb/s, 1.2 TB, 10,000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 3.5-inch, business critical
HDD SAS, 6 Gb/s, 1 TB, 7,200 rpm, hot-plug, 2.5-inch, business critical

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu PRIMERGY RX350 S8, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY RX350 S8, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.